



COMPACT WHEEL SKID STEER LOADER

KEY SPECIFICATIONS

RATED LOAD CAPACITY

380 kg

BUCKET CAPACITY

0.2 m³

DUMPING HEIGHT

2000 mm

ENGINE	OPERATING WEIGHT	MAX SPEED	GROUND CLEARANCE
18.2kW / 3000rpm	1300 kg	8 km/h	145 mm

FEATURES & ADVANTAGES

Powerful Diesel Engine

Kubota/Perkins D1105 diesel engine delivering 18.2kW at 3000rpm for reliable everyday performance.

Hydraulic Bucket Tipping

40 degree max dumping angle with a 2000mm dumping height for efficient loading and unloading.

High Load Capacity

Rated to carry 380kg with a 0.2m³ bucket, suited to landscaping and light construction sites.

Compact Turning Circle

Front turning radius of 1660mm makes this loader easy to maneuver in tight yard spaces.

All-Terrain Wheels

6.50-10 tyres provide solid traction and a smooth ride on hard and semi-firm ground.

Fast Cycle Times

7 second boom lift time and 50 L/min hydraulic flow keep loading cycles quick and efficient.

DIESEL ENGINE | HYDRAULIC LOADER ARM | WHEELED UNDERCARRIAGE



Front View



Rear View

TECHNICAL SPECIFICATIONS

PERFORMANCE DATA	
Operating Weight	1300 kg
Rated Load	380 kg
Bucket Capacity	0.2 m ³
Max Traction	≥ 12 kN
Max Breakout Force	≥ 7.3 kN
Boom Lifting Time	7 s
Rated Hydraulic Flow	50 L/min
High Flow Flux	N/A
Tyre Model	6.50-10
Fuel Tank Capacity	28 L
Max Travel Speed	8 km/h
ENGINE DATA	
Manufacturer	Kubota / Perkins
Engine Model	D1105 / 403J-11
Rated Power	18.2 kW / 3000 rpm
Displacement	1.123 L
Emission Standard	Euro 5 / EPA 4

DIMENSION DATA (A-U)	
A. Overall Operating Height	3400 mm
B. Height to Bucket Hinge Pin	2500 mm
C. Height to Top of Cab	1813 mm
D. Height to Bottom of Level Bucket	2446 mm
E. Length without Bucket	2200 mm
F. Overall Length with Bucket	2950 mm
G. Max Dumping Angle	40°
H. Dumping Height	2000 mm
I. Dumping Reach	441 mm
J. Bucket Rollback (Ground)	30°
K. Bucket Rollback (Full Height)	103°
L. Wheelbase	801 mm
M. Ground Clearance	145 mm
N. Angle of Departure	20°
O. Turning Radius (no bucket)	960 mm
P. Front Turning Radius	1660 mm
Q. Rear Turning Radius	1253 mm
R. Rear Axle to Bumper	910 mm
S. Tread Width	785 mm
T. Overall Width	920 mm
U. Bucket Width	1070 mm

Specifications subject to change without notice. Pricing available on request.